www.EUROPOWERGenerators.com

EP14TDE

Article code: 981111403





Europower open generating sets with Kubota water-cooled diesel engines, 1500rpm, 50Hz, 4 stroke

Generator:

kVA max.: 14 kVA cont.: 13

kVA: 4.3kVA @ 1~230V 13kVA @ 3~400V Amps cont.: 19A @ 1~230V 19A @ 3~400V

Dimensions I x w x h: 150x74x89cm

Dry weight: 399kg

Weight incl. oil (+ coolant if water-

cooled), excl. fuel:

410kg

Weight incl. oil (+ coolant if water-

cooled) + fuel:

465kg

Engine:

Brand/Type: Kubota D1703M E4BG2-EUP-1

HP max.: 20

Power: 15kW max. (1500rpm), 3-cylinder

Diesel, Water-cooled

Displacement: 1647cm³

Consumption @75% load: 2.6 litres/hour

Tank: 65 litres
Autonomy @75% load: 25 hours

Noise level: 73dB(A)@7m (*)

Electronic speed governor:

EU Emission norm:

Stage V

Battery voltage:

CO2 emission:

Standard

Stage V

0 g/kWh

Alternator:

in vehicles, please contact us.

Brand/Type Leroy Somer LSA40S3 - 15/16.5kVA 230/400V - brushless

Nominal voltage: 3~400V and 1~230V

Frequency: 50Hz
Protection degree: IP23

Generators with * cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators

www.EdropowerGenerators.com

Version:

- 1 socket 230V 16A + 1 socket CEE 230V 32A + 1 socket CEE 400V 16A 5 p.
- Automatic voltage regulator
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Electronic speed governor
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Leroy Somer alternator System 2 for tropical environment
- Low oil pressure control lamp
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter



Your **EUROPOWER** dealer