


EP193DE

Article code: 951011901



Europower open generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

kVA max.:	17.8
kVA cont.:	16.2
kVA:	16kVA @ 1~230V 0kVA @ 3~400V
Amps cont.:	70A @ 1~230V 0A @ 3~400V
Dimensions l x w x h:	150x74x89cm
Weight incl. oil (+ coolant if water-cooled), excl. fuel:	370kg
Weight incl. oil (+ coolant if water-cooled) + fuel:	425kg

Engine:

Brand/Type:	Kubota V1505 E2B-EUP-1
HP max.:	36
Power:	27kW max. (3000rpm), 4-cylinder Diesel, Water-cooled
Displacement:	1498cm ³
Consumption @75% load:	5 litres/hour
Tank:	65 litres
Autonomy @75% load:	13 hours
Noise level:	83dB(A)@7m (*)
EU Emission norm:	Non emission IIIa
Battery voltage:	12V
CO2 emission:	0 g/kWh

Alternator:

Brand/Type	Sincro GK2MBL - IP21 - brushless
Nominal voltage:	3~400V and 1~230V
Frequency:	50Hz
Protection degree:	IP21

www.EUROPOWERGenerators.com

Generators with * cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators in vehicles, please contact us.

At present all EU portable generators in the power range from 18 to 560kVA are required to meet Stage IIIA regulations. A portable generator is either a rental set or a unit that is moved more than twice a year. The EU does not regulate emissions from stationary diesel generators used for prime power, peak shaving or emergency standby power.

Version:

- 1 socket 230V - 16A + 1 socket CEE 230V - 63A
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

www.EUROPOWERGenerators.com



Your **EUROPOWER** dealer