www.EUROPOWERGenerators.com

<u>EP73DE</u>

Article code: 951010601





Europower open generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

kVA cont.: 5.4 kVA: 5.4kVA @ 1~230V 0kVA @ 3~400V Amps cont.: 23A @ 1~230V 0A @ 3~400V Dimensions I x w x h: 105x64x78cm Dry weight: 183kg Weight incl. oil (+ coolant if water-cooled), excl. fuel: 190kg Weight incl. oil (+ coolant if water-cooled) + fuel: 230kg Fand/Type: Kubota Z482 E4B-EUP-1 HP max.: 10.2 Power: 7.5kW max. (3000rpm), 2-cylinder Displacement: 479cm ³ Consumption @75% load: 1.8 litres/hour Tank: 47 litres Autonony @75% load: 26.1 hours Noise level: 78dB(A)@7m (*) EU Emission norm: Stage V Battery voltage: 12V CO2 emission: 0 g/kWh Alternator: Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushless Nominal voltage: 3~400V and 1~230V Frequency: 50Hz	kVA max.:	6
Amps cont.: 23A @ 1~230V 0A @ 3~400V Dimensions I x w x h: 105x64x78cm Dry weight: 183kg Weight incl. oil (+ coolant if water-cooled), excl. fuel: 190kg Weight incl. oil (+ coolant if water-cooled) + fuel: 230kg Engine: Brand/Type: Brand/Type: Kubota Z482 E4B-EUP-1 HP max.: 10.2 Power: 7.5kW max. (3000rpm), 2-cylinder Displacement: 479cm³ Consumption @75% load: 1.8 litres/hour Tank: 47 litres Autonomy @75% load: 26.1 hours Noise level: 78dB(A)@7m (*) EU Emission norm: Stage V Battery voltage: 12V CO2 emission: 0 g/kWh Autonomy @75% load: 3~400V and 1~230V Frequency: 50Hz	kVA cont.:	5.4
Dimensions I x w x h:105x64x78cmDry weight:183kgWeight incl. oil (+ coolant if water- cooled), excl. fuel:190kgWeight incl. oil (+ coolant if water- cooled) + fuel:230kgEngine: Brand/Type:Kubota Z482 E4B-EUP-1HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinderDiesel, Water-cooledDiesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAtternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	kVA:	5.4kVA @ 1~230V 0kVA @ 3~400V
Dry weight:183kgWeight incl. oil (+ coolant if water- cooled), excl. fuel:190kgWeight incl. oil (+ coolant if water- cooled) + fuel:230kgEngine:Weight incl. oil (+ coolant if water- cooled) + fuel:10.2Brand/Type:10.2Power:7.5kW max. (3000rpm), 2-cylinder Diesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhKiternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Amps cont.:	23A @ 1~230V 0A @ 3~400V
Weight incl. oil (+ coolant if water- cooled), excl. fuel:190kgWeight incl. oil (+ coolant if water- cooled) + fuel:230kgEngine:Xubota Z482 E4B-EUP-1HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinder Diesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAtternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Dimensions l x w x h:	105x64x78cm
cooled), excl. fuel:190kgWeight incl. oil (+ coolant if water- cooled) + fuel:230kgEngine:230kgBrand/Type:Kubota Z482 E4B-EUP-1HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinderDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Dry weight:	183kg
cooled) + fuel:230kgEngine:Kubota Z482 E4B-EUP-1Brand/Type:Kubota Z482 E4B-EUP-1HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinderDiesel, Water-cooledDiesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:2VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz		190kg
Brand/Type:Kubota Z482 E4B-EUP-1HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinderDiesel, Water-cooledDiesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz		230kg
HP max.:10.2Power:7.5kW max. (3000rpm), 2-cylinderDiesel, Water-cooledDiesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhGinro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Engine:	
Power:7.5kW max. (3000rpm), 2-cylinder Diesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Brand/Type:	Kubota Z482 E4B-EUP-1
Diesel, Water-cooledDisplacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Brand/TypeSincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	HP max.:	10.2
Displacement:479cm³Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhSincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Power:	7.5kW max. (3000rpm), 2-cylinder
Consumption @75% load:1.8 litres/hourTank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Brand/TypeSincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz		Diesel, Water-cooled
Tank:47 litresAutonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Displacement:	479cm ³
Autonomy @75% load:26.1 hoursNoise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Consumption @75% load:	1.8 litres/hour
Noise level:78dB(A)@7m (*)EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Tank:	47 litres
EU Emission norm:Stage VBattery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Autonomy @75% load:	26.1 hours
Battery voltage:12VCO2 emission:0 g/kWhAlternator:Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	Noise level:	78dB(A)@7m (*)
CO2 emission: 0 g/kWh Alternator: Brand/Type Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushless Nominal voltage: 3~400V and 1~230V Frequency: 50Hz	EU Emission norm:	Stage V
Alternator:Brand/TypeSincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz		12V
Brand/TypeSincro EK2LCT - 8kVA SAE5/6.5 230V - brushlessNominal voltage:3~400V and 1~230VFrequency:50Hz	CO2 emission:	0 g/kWh
Nominal voltage:3~400V and 1~230VFrequency:50Hz	Alternator:	
Frequency: 50Hz	Brand/Type	Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushless
	Nominal voltage:	3~400V and 1~230V
Drataction degrady ID22		
Flotection degree. IF25	Protection degree:	IP23

Generators with * cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators in vehicles, please contact us.

Version:

- 1 socket 230V 16A + 1 socket CEE 230V 32A
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter



Your EUROPOWER dealer