


EPS183TDE

Article code: 991011814



Europower super-silenced generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

| | |
|-----------------------------------------------------------|-----------------------------------|
| KVA max.: | 18 |
| kVA cont.: | 17 |
| kVA: | 6.3kVA @ 1~230V 17kVA @ 3~400V |
| Amps cont.: | 27A @ 1~230V 25A @ 3~400V |
| Dimensions l x w x h: | 150x64x90cm |
| Dry weight: | 441kg |
| Weight incl. oil (+ coolant if water-cooled), excl. fuel: | 450kg |
| Weight incl. oil (+ coolant if water-cooled) + fuel: | 503kg |

Engine:

| | |
|------------------------|---------------------------------------------------------|
| Brand/Type: | Kubota D1105 E4B-EUP-1 |
| HP max.: | 23 |
| Power: | 17kW max. (3000rpm), 3-cylinder Diesel, Water-cooled |
| Displacement: | 1123cm ³ |
| Consumption @75% load: | 3.9 litres/hour |
| Tank: | 63 litres |
| Autonomy @75% load: | 16.2 hours |
| Noise level: | 71dB(A)@7m = Lwa 96 |
| EU Emission norm: | Stage V |
| Battery voltage: | 12V |
| CO2 emission: | 0 g/kWh |

Alternator:

| | |
|--------------------|----------------------------------------|
| Brand/Type | Mecc Alte ECP3-2L/2 - brushless |
| Nominal voltage: | 3~400V and 1~230V |
| Frequency: | 50Hz |
| Protection degree: | IP23 |

Version:

- 2 sockets 230V - 16A + 1 socket CEE 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 400V - 16A 5 p. + 1 socket CEE 400V - 32A 5 p.
- Automatic voltage regulator
- Central lifting eye
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mecc Alte alternator Total+ for tropical environment
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

Powered by:



Your **EUROPOWER** dealer