


EPS193DE

Article code: 951011911



Europower super-silenced generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

kVA max.:	17.8
kVA cont.:	16.2
kVA:	16kVA @ 1~230V 0kVA @ 3~400V
Amps cont.:	70A @ 1~230V 0A @ 3~400V
Dimensions l x w x h:	170x74x100cm
Weight incl. oil (+ coolant if water-cooled), excl. fuel:	545kg
Weight incl. oil (+ coolant if water-cooled) + fuel:	607kg

Engine:

Brand/Type:	Kubota V1505 E2B-EUP-1
HP max.:	36
Power:	27kW max. (3000rpm), 4-cylinder Diesel, Water-cooled
Displacement:	1498cm ³
Consumption @75% load:	5 litres/hour
Tank:	73 litres
Autonomy @75% load:	14.6 hours
Noise level:	71dB(A)@7m = Lwa 96
EU Emission norm:	Non emission IIIa
Battery voltage:	12V
CO2 emission:	0 g/kWh

Alternator:

Brand/Type	Sincro GK2MBL - IP21 - brushless
Nominal voltage:	3~400V and 1~230V
Frequency:	50Hz
Protection degree:	IP21

www.EUROPOWERGenerators.com

At present all EU portable generators in the power range from 18 to 560kVA are required to meet Stage IIIA regulations. A portable generator is either a rental set or a unit that is moved more than twice a year. The EU does not regulate emissions from stationary diesel generators used for prime power, peak shaving or emergency standby power.

Version:

- 1 socket 230V - 16A + 1 socket CEE 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 230V - 63A
- Central lifting eye
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

www.EUROPOWERGenerators.com



Your **EUROPOWER** dealer