



USE

For the MITER cut of porcelain tiles.

High STABILITY and SPEED of cut.

Respect ALWAYS tile's original edge.

Wet cut.

DIAMOND BLADE CHARACTERISTICS

Sintered TURBO blade.

Laser welding.

Suitable for use in wet tile saws that incorporate a protection system in accordance with standard for the use of segmented blades.

www.rubi.com



COMMON TECHNICAL SPECIFICATIONS

SUPERPRO quality.

Rim height: 7.5 mm.

Inner diameter: 25.4 mm (Ref. 31967 includes reduction ring to 22.2 mm).

Rim thickness: 2.5 mm.

Maximum perimeter speed: 80 m/s.

OWN TECHNICAL SPECIFICATIONS

Ref. 31966 – Ø200 SUPERPRO: Maximum RPM: 7,650.

Ref. 31967 – Ø230 SUPERPRO: Maximum RPM: 6,650.

Ref. 31969 – Ø250 SUPERPRO: Maximum RPM: 6,150.

PACKAGING

Full-colour carton blister with anti-theft clipping system.

Blister dimensions:

Ref. 31966 - Ø200: 24.5x21 mm.

Ref. 31967/31969 – Ø230/250: 30x26 mm.

Sales unit: 1 blister.

NORM

Conform to EN-13236.

www.rubi.com